

The Dutch Accreditation Council RvA, by law appointed as the national accreditation body for The Netherlands, hereby declares that accreditation has been granted to:

TRESCAL Hengelo B.V. Calibration Laboratory Hengelo

The organisation has demonstrated to be able to generate technical valid results in a competent way and work according to a management system.

This accreditation is based on an assessment against the requirements as laid down in EN ISO/IEC 17025:2017.

The accreditation covers the activities as specified in the authorized annex bearing the registration number.

The accreditation is valid provided that the organisation continues to meet the requirements.

The accreditation with registration number:

K 018

is granted on 15 September 1980

This declaration is valid until

1 December 2024

The board of the Dutch Accreditation Council, on its behalf.

mr. J.A.W.M. de Haas

Annex to declaration of accreditation (scope of accreditation)

Normative document: EN ISO/IEC 17025:2017

Registration number: K 018

of TRESCAL Hengelo B.V. Calibration Laboratory

This annex is valid from: **21-01-2021** to **01-12-2024** Replaces annex dated: **05-06-2020**

HCS code	Measured quantity, Instrument, Measure	Frequency	CMC ¹	Remarks	Location
	19 Ω , 100 Ω , 190 Ω , 1 $k\Omega$, 1.9 $k\Omega$, 10 $k\Omega$, 19 $k\Omega$, 100 $k\Omega$, 190 $k\Omega$		2.0•10 ⁻⁵ •R	Generate	
	1 ΜΩ, 1.9 ΜΩ		3•10 ⁻⁵ •R	Generate	
	10 ΜΩ		4•10 ⁻⁵ •R	Generate	
	19 ΜΩ, 100 ΜΩ		6•10 ⁻⁵ • <i>R</i>	Generate	
LF 6 5	LF Capacity				HLO, OS
	2 nF, 10 nF, 20 nF, 200 nF	1 kHz	1.0•10 ⁻³ • <i>C</i>	Generate only sine-shaped signals	

HCS code	Measured quantity, Instrument, Measure	Range	CMC ¹	Remarks	Location
PV 1 0	Gas pressure				
PV 1 1	Absolute pressure	(750 - 1150) hPa a	0.3 hPa	By comparison to a reference barometer	HLO
		(0.01 – 1.1) MPa a	0.3 hPa + 25•10 ⁻⁵ •(<i>p</i> -100 kPa))		
		(1.1 – 60.1) MPa a	1•10 ⁻³ •(<i>p</i> -0.1 MPa))	By comparison with digital pressure indicators	HLO, OS
PV 1 2	Relative pressure	(-1.590) kPa g	25•10 ⁻⁵ • <i>p</i> e		HLO
		(1.5 - 1000) kPa g	25•10 ⁻⁵ • <i>p</i> e		
		(1 - 60) MPa g	1•10 ⁻³ • <i>p</i> e	By comparison with digital pressure indicators	HLO, OS
PV 2 0	Liquid pressure				

Dutch Accreditation Council RvA

Annex to declaration of accreditation (scope of accreditation)

Normative document: EN ISO/IEC 17025:2017

Registration number: K 018

of TRESCAL Hengelo B.V. Calibration Laboratory

This annex is valid from: **21-01-2021** to **01-12-2024** Replaces annex dated: **05-06-2020**

HCS code	Measured quantity, Instrument, Measure	Range	CMC ¹	Remarks	Location
PV 2 1	Absolute pressure	(120 - 300) kPa a	0.3 hPa + 1•10 ⁻³ •(<i>p</i> -100 kPa)	By comparison with digital pressure indicators	HLO, OS
		(0.3 – 70.1) MPa a	0.3 hPa + 25•10 ⁻⁵ •(<i>p</i> -0.1 MPa)		
PV 2 2	Relative pressure	(20 - 200) kPa g	1•10 ⁻³ • <i>p</i> e	By comparison with	HLO, OS
		(0.2 - 70) MPa g	25•10 ⁻⁵ • <i>p</i> e	digital pressure indicators	
TE 1 0	Resistance thermometer with and without readout	-20 °C up to 250 °C	0.10 °C	By comparison in liquid block baths with external reference probe	HLO, OS
		250 °C up to 650 °C	0.20 °C		
TE 3 0	Thermocouple with and without readout	-20 °C up to 250 °C	0.10 °C	By comparison in liquid block baths with external reference probe	HLO, OS
		250 °C up to 650 °C	0.20 °C		
TF 2 0	Relative time				HLO
	Electronic chronometers	24 h	0.1 s / 24 h	Direct measurement	
	Mechanical chronometers	24 h	5 s / 24 h	Direct measurement	
TF 2 1	Time and Frequency				HLO
	10 Hz – 225 MHz		3•10 ⁻⁶ •f	Measure	
TF 2 2	Time interval				HLO

Dutch Accreditation Council RvA Page 17 of 18